

| | | | | | | |
|---|---|---|---|---|---|---|
| | | | | | | |
| DOOR TAG (EXD-01) | DOOR TAG (EXD-02) | DOOR TAG (EXD-03) | DOOR TAG (EXD-04) | DOOR TAG (EXD-05) | DOOR TAG (EXD-06) | DOOR TAG (EXD-07) |
| LOCATION ALL FLOORS; FIRE EXIT | LOCATION BASEMENT-24TH FLOOR; UTILITY | LOCATION BASEMENT-24TH FLOOR; TOILET ROOM | LOCATION BASEMENT, 7TH, 8TH, 10TH FLOORS; BALCONY | LOCATION 7TH, 9TH, 11TH-24TH FLOOR; BALCONY | LOCATION ELECTRICAL PIPE CHASE ACCESS | LOCATION GROUND FLOOR; ENTRANCE |
| DESCRIPTION FIRE-RATED METAL DOOR; SINGLE LEAF, SINGLE SWING DOOR W/ VISION PANEL | DESCRIPTION HOLLOW METAL DOOR; SINGLE LEAF, SINGLE SWING DOOR | DESCRIPTION HOLLOW METAL DOOR; SINGLE LEAF, SINGLE SWING DOOR W/ LOUVER | DESCRIPTION FRAMED GLASS DOOR; SINGLE LEAF, SINGLE SWING DOOR | DESCRIPTION FRAMED GLASS DOOR; DOUBLE LEAF, SINGLE SWING DOOR | DESCRIPTION HOLLOW METAL DOOR; DOUBLE LEAF, SINGLE SWING DOOR W/ LOUVER | DESCRIPTION LOUVERED METAL DOOR; DOUBLE LEAF, SINGLE SWING DOOR |
| FINISHES -PRIMED AND AUTOMOTIVE SPRAY PAINT -VISION PANEL: VP-2 150 X 750MM IN 1 1/2 HOUR FIRE-RATED TEMPERED GLASS ON FIRE RATED GLAZING BEAD | FINISHES -PRIMED AND AUTOMOTIVE SPRAY PAINT | FINISHES -PRIMED AND AUTOMOTIVE SPRAY PAINT | FINISHES -PRIMED AND AUTOMOTIVE SPRAY PAINT -TEMPERED CLEAR GLASS | FINISHES -PRIMED AND AUTOMOTIVE SPRAY PAINT -TEMPERED CLEAR GLASS | FINISHES -PRIMED AND AUTOMOTIVE SPRAY PAINT | FINISHES -PRIMED AND AUTOMOTIVE SPRAY PAINT |
| HARDWARE -TOP AND BOTTOM CONCEALED HINGES/CLOSER WITH TOP AND BOTTOM MORTISE FLUSH BOLT. -HEAVY DUTY CYLINDRICAL LEVER KEYED-LOCKSET SATIN CHROMIUM PLATED FINISH -COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE -TOP AND BOTTOM CONCEALED HINGES/CLOSER WITH TOP AND BOTTOM MORTISE FLUSH BOLT. -HEAVY DUTY CYLINDRICAL LEVER KEYED-LOCKSET SATIN CHROMIUM PLATED FINISH -COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE -TOP AND BOTTOM CONCEALED HINGES/CLOSER WITH TOP AND BOTTOM MORTISE FLUSH BOLT. -HEAVY DUTY CYLINDRICAL LEVER KEYED-LOCKSET SATIN CHROMIUM PLATED FINISH -COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE -TOP AND BOTTOM CONCEALED HINGES/CLOSER WITH TOP AND BOTTOM MORTISE FLUSH BOLT. -HEAVY DUTY CYLINDRICAL LEVER KEYED-LOCKSET SATIN CHROMIUM PLATED FINISH -COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE -TOP AND BOTTOM CONCEALED HINGES/CLOSER WITH TOP AND BOTTOM MORTISE FLUSH BOLT. -HEAVY DUTY CYLINDRICAL LEVER KEYED-LOCKSET SATIN CHROMIUM PLATED FINISH -COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE -TOP AND BOTTOM CONCEALED HINGES/CLOSER WITH TOP AND BOTTOM MORTISE FLUSH BOLT. -HEAVY DUTY CYLINDRICAL LEVER KEYED-LOCKSET SATIN CHROMIUM PLATED FINISH -COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE -TOP AND BOTTOM CONCEALED HINGES/CLOSER WITH TOP AND BOTTOM MORTISE FLUSH BOLT. -HEAVY DUTY CYLINDRICAL LEVER KEYED-LOCKSET SATIN CHROMIUM PLATED FINISH -COMPLETE WITH STANDARD PARTS AND ACCESSORIES. |
| JAMB/FRAME PRIMED AND PAINTED 2-HOUR FIRE-RATED JAMB | JAMB/FRAME PRIMED AND PAINTED 2-HOUR FIRE-RATED JAMB | JAMB/FRAME PRIMED AND PAINTED 2-HOUR FIRE-RATED JAMB | JAMB/FRAME POWDER COATED ALUMINUM DOOR JAMB | JAMB/FRAME POWDER COATED ALUMINUM DOOR JAMB | JAMB/FRAME PRIMED AND PAINTED 2-HOUR FIRE-RATED STEEL JAMB | JAMB/FRAME PRIMED AND PAINTED 2-HOUR FIRE-RATED STEEL JAMB |
| NO. OF SETS 51 SETS; VERIFY | NO. OF SETS 132 SETS; VERIFY | NO. OF SETS 45 SETS; VERIFY | NO. OF SETS 15 SETS; VERIFY | NO. OF SETS 43 SETS; VERIFY | NO. OF SETS 46 SETS; VERIFY | NO. OF SETS 3 SETS; VERIFY |
| NOTE EXISTING ON SITE | NOTE EXISTING ON SITE | NOTE EXISTING ON SITE | NOTE EXISTING ON SITE | NOTE EXISTING ON SITE | NOTE EXISTING ON SITE | NOTE EXISTING ON SITE |
| | | | | | | |
| DOOR TAG (GD-01) | DOOR TAG (GD-02) | DOOR TAG (GD-03) | DOOR TAG (SD-01) | DOOR TAG (SD-02) | DOOR TAG (SD-03) | DOOR TAG (SD-04) |
| LOCATION GROUND, 7TH-24TH FLOOR; MEETING ROOM | LOCATION GROUND, 7TH-24TH FLOOR; MEETING ROOM | LOCATION 8TH, 10TH-12TH, 15TH, 17TH-23RD FLOOR; KITCHEN | LOCATION MALE & FEMALE CHANGING ROOM | LOCATION 7TH FLOOR; KITCHEN | LOCATION 7TH-8TH, 11TH-23RD FLOOR; PANTRY, STORAGE | LOCATION PLUMBING PIPE CHASE |
| DESCRIPTION FRAMELESS GLASS DOOR; SINGLE LEAF, SINGLE SWING DOOR | DESCRIPTION FRAMELESS GLASS DOOR; DOUBLE LEAF, SINGLE SWING DOOR | DESCRIPTION SLIDING GLASS DOOR; DOUBLE LEAF, DOUBLE ACTION GLASS DOOR | DESCRIPTION HOLLOW METAL DOOR; SINGLE LEAF, SINGLE SWING DOOR W/ LOUVER | DESCRIPTION HOLLOW METAL DOOR; DOUBLE LEAF, DOUBLE SWING DOOR | DESCRIPTION HOLLOW METAL DOOR; UNEVEN LEAF, SINGLE SWING DOOR | DESCRIPTION HOLLOW METAL DOOR; SINGLE LEAF, SINGLE SWING DOOR W/ LOUVER |
| FINISHES -TEMPERED CLEAR GLASS | FINISHES -TEMPERED CLEAR GLASS | FINISHES -TEMPERED CLEAR GLASS | FINISHES -PRIMED AND AUTOMOTIVE SPRAY PAINT | FINISHES -PRIMED AND AUTOMOTIVE SPRAY PAINT | FINISHES -PRIMED AND AUTOMOTIVE SPRAY PAINT | FINISHES -PRIMED AND AUTOMOTIVE SPRAY PAINT |
| HARDWARE -STAINLESS STEEL HAIRLINE FINISH DOOR PULL | HARDWARE -STAINLESS STEEL HAIRLINE FINISH DOOR PULL | HARDWARE -TOP AND BOTTOM CONCEALED HINGES/CLOSER WITH TOP AND BOTTOM MORTISE FLUSH BOLT. -HEAVY DUTY CYLINDRICAL LEVER KEYED-LOCKSET SATIN CHROMIUM PLATED FINISH -COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE -TOP AND BOTTOM CONCEALED HINGES/CLOSER WITH TOP AND BOTTOM MORTISE FLUSH BOLT. -HEAVY DUTY CYLINDRICAL LEVER KEYED-LOCKSET SATIN CHROMIUM PLATED FINISH -COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE -TOP AND BOTTOM CONCEALED HINGES/CLOSER WITH TOP AND BOTTOM MORTISE FLUSH BOLT. -HEAVY DUTY CYLINDRICAL LEVER KEYED-LOCKSET SATIN CHROMIUM PLATED FINISH -COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE -TOP AND BOTTOM CONCEALED HINGES/CLOSER WITH TOP AND BOTTOM MORTISE FLUSH BOLT. -HEAVY DUTY CYLINDRICAL LEVER KEYED-LOCKSET SATIN CHROMIUM PLATED FINISH -COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE -TOP AND BOTTOM CONCEALED HINGES/CLOSER WITH TOP AND BOTTOM MORTISE FLUSH BOLT. -HEAVY DUTY CYLINDRICAL LEVER KEYED-LOCKSET SATIN CHROMIUM PLATED FINISH -COMPLETE WITH STANDARD PARTS AND ACCESSORIES. |
| JAMB/FRAME FRAMELESS DOOR, NO JAMB | JAMB/FRAME FRAMELESS DOOR, NO JAMB | JAMB/FRAME POWDER COATED ALUMINUM DOOR JAMB | JAMB/FRAME PRIMED AND PAINTED STEEL JAMB | JAMB/FRAME PRIMED AND PAINTED STEEL JAMB | JAMB/FRAME PRIMED AND PAINTED STEEL JAMB | JAMB/FRAME 40mm X 100mm PVC DOOR FRAME |
| NO. OF SETS GD-01 (58 SETS), GD-01a (2 SETS); VERIFY | NO. OF SETS GD-02 (115 SETS), GD-02a (1 SET); VERIFY | NO. OF SETS 19 SETS; VERIFY | NO. OF SETS 2 SETS; VERIFY | NO. OF SETS 3 SETS; VERIFY | NO. OF SETS 39 SETS; VERIFY | NO. OF SETS 48 SETS; VERIFY |
| NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. |
| | | | | | | |
| DOOR TAG (PVC-01) | DOOR TAG (WD-01) | DOOR TAG (WD-02) | DOOR TAG (WD-03) | DOOR TAG (WD-04) | | |
| LOCATION 8TH, 10TH-12TH, 15TH, 17TH-24TH FLOOR; TOILET AND BATH | LOCATION GROUND, 7TH-23RD FLOOR; STORAGE ROOM | LOCATION GROUND, 7TH-9TH, 24TH FLOOR; STORAGE ROOM | LOCATION 7TH, 9TH, 11TH-23RD FLOOR; OFFICES | LOCATION 7TH-23RD FLOOR; OFFICES | | |
| DESCRIPTION PVC DOOR; SINGLE LEAF, SINGLE SWING DOOR PANEL W/ LOUVER VENT | DESCRIPTION SOLID WOOD DOOR; SINGLE LEAF, SINGLE SWING DOOR PANEL | DESCRIPTION SOLID WOOD DOOR; DOUBLE LEAF, SINGLE SWING DOOR PANEL | DESCRIPTION SOLID CORE WOOD DOOR; SINGLE LEAF, SINGLE SWING DOOR W/ VISION PANEL | DESCRIPTION SOLID CORE WOOD DOOR; DOUBLE LEAF, SINGLE SWING DOOR W/ VISION PANEL | | |
| FINISHES -PVC DOOR | FINISHES -44mm THICK WOOD DOOR, OIL STAINED TOP WITH CLEAR GLOSS LACQUER TOP COAT FINISH | FINISHES -44mm THICK WOOD DOOR, OIL STAINED TOP WITH CLEAR GLOSS LACQUER TOP COAT FINISH | FINISHES -HIGH-PRESSURE LAMINATE -VISION PANEL: VP-1 150 X 2100MM IN 6MM THK TEMPERED GLASS ON CLEAR ANODIZED GLAZING BEAD | FINISHES -HIGH-PRESSURE LAMINATE -VISION PANEL: VP-1 150 X 2100MM IN 6MM THK TEMPERED GLASS ON CLEAR ANODIZED GLAZING BEAD | | |
| HARDWARE -TOP AND BOTTOM CONCEALED HINGES/CLOSER WITH TOP AND BOTTOM MORTISE FLUSH BOLT. -HEAVY DUTY CYLINDRICAL LEVER KEYED-LOCKSET SATIN CHROMIUM PLATED FINISH -COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE -TOP AND BOTTOM CONCEALED HINGES/CLOSER WITH TOP AND BOTTOM MORTISE FLUSH BOLT. -HEAVY DUTY CYLINDRICAL LEVER KEYED-LOCKSET SATIN CHROMIUM PLATED FINISH -COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE -TOP AND BOTTOM CONCEALED HINGES/CLOSER WITH TOP AND BOTTOM MORTISE FLUSH BOLT. -HEAVY DUTY CYLINDRICAL LEVER KEYED-LOCKSET SATIN CHROMIUM PLATED FINISH -COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE -TOP AND BOTTOM CONCEALED HINGES/CLOSER WITH TOP AND BOTTOM MORTISE FLUSH BOLT. -HEAVY DUTY CYLINDRICAL LEVER KEYED-LOCKSET SATIN CHROMIUM PLATED FINISH -COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE -TOP AND BOTTOM CONCEALED HINGES/CLOSER WITH TOP AND BOTTOM MORTISE FLUSH BOLT. -HEAVY DUTY CYLINDRICAL LEVER KEYED-LOCKSET SATIN CHROMIUM PLATED FINISH -COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | | |
| JAMB/FRAME 40mm X 100mm PVC DOOR FRAME | JAMB/FRAME 40mm X 100mm KILN DRY, S4S WOOD TANGULE. | JAMB/FRAME 40mm X 100mm KILN DRY, S4S WOOD TANGULE. | JAMB/FRAME 40mm X 100mm KILN DRY, S4S WOOD TANGULE. | JAMB/FRAME 40mm X 100mm KILN DRY, S4S WOOD TANGULE. | | |
| NO. OF SETS 51 SETS; VERIFY | NO. OF SETS WD-01 (66 SETS), WD-01a (2 SETS); VERIFY | NO. OF SETS 10 SETS; VERIFY | NO. OF SETS 53 SETS; VERIFY | NO. OF SETS 88 SETS; VERIFY | | |
| NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | | |

1 SCHEDULE OF DOORS
SCALE 1:50 W.

NOTE:
PURSUANT TO SECTION 4 OF ANNEX "A" OF THE REVISED IMPLEMENTING RULES AND REGULATIONS OF R.A. 9164, APPROVAL BY THE AUTHORIZED DPWH OFFICIALS OF DETAILED ENGINEERING SURVEYS AND DESIGN UNDERTAKEN BY CONSULTANTS NEITHER CHANGES THE RESPONSIBILITY OF THE LATTER FOR THE TECHNICAL INTEGRITY OF THE SURVEYS AND DESIGN NOR TRANSFER ANY PART OF THAT RESPONSIBILITY TO THE APPROVING OFFICIALS.
THE DESIGN CONSULTANT SHALL BE HELD RESPONSIBLE FOR THE FAILURE OF THE FACILITY/IES / STRUCTURES DUE TO FAULTY DESIGN EXCEPT FOR THE CHANGES MADE WITHOUT THE CONFORMITY OF THE CONSULTANTS.

DRAWINGS AND SPECIFICATIONS DULY SIGNED, STAMPED OR SEALED, AS INSTRUMENTS OF SERVICE ARE PROPERTY AND DOCUMENTS OF THE ARCHITECT, WHETHER THE OBJECT FOR WHICH THEY ARE MADE IS EXECUTED OR NOT. IT SHALL BE UNLAWFUL FOR ANY PERSON, WITHOUT THE WRITTEN CONSENT OF THE ARCHITECT OR AUTHOR OF SAID DOCUMENTS, TO DUPLICATE OR TO MAKE COPIES OF SAID DOCUMENTS FOR USE IN THE REPLICATION OF AND FOR OTHER PROJECTS OR BUILDINGS, WHETHER EXECUTED PARTLY OR IN WHOLE.

| | | | |
|--|--|--|--|
| | | | |
| DOOR TAG (BD-01) | DOOR TAG (BD-02) | DOOR TAG (BD-03) | DOOR TAG (BD-04) |
| LOCATION 9TH FLOOR MEDIA ROOM/ PRESS CONFERENCE ROOMS | LOCATION CONFERENCE/ BOARD ROOMS | LOCATION CONFERENCE/ BOARD ROOMS | LOCATION 11TH FLOOR STORAGE |
| DESCRIPTION 71mm THK OPERABLE WALL PANEL WITH 40 STC | DESCRIPTION 71mm THK OPERABLE WALL PANEL WITH 40 STC | DESCRIPTION 71mm THK OPERABLE WALL PANEL WITH 40 STC | DESCRIPTION 71mm THK OPERABLE WALL PANEL WITH 40 STC |
| FINISHES HIGH PRESSURE LAMINATE ON 6mm THK MARINE PLYWOOD BACKING | FINISHES HIGH PRESSURE LAMINATE ON 6mm THK MARINE PLYWOOD BACKING | FINISHES HIGH PRESSURE LAMINATE ON 6mm THK MARINE PLYWOOD BACKING | FINISHES HIGH PRESSURE LAMINATE ON 6mm THK MARINE PLYWOOD BACKING |
| HARDWARE - 4mm X 76mm X 80mm HEAVY DUTY ALUMINUM TRACK AND HARD PLASTIC ROLLERS - 2 ROLLER PER PANEL CARRIER SYSTEM - SOSS HINGES FOR DOOR PANEL - ROCKWOOL INSULATION - MANUAL OPERATED RETRACTABLE TOP AND BOTTOM CRANKING SEAL - ROTATABLE TYPE END PANEL CLOSURE - PROVIDE STRUCTURAL SUPPORT FOR THE TRACKS COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE - 4mm X 76mm X 80mm HEAVY DUTY ALUMINUM TRACK AND HARD PLASTIC ROLLERS - 2 ROLLER PER PANEL CARRIER SYSTEM - SOSS HINGES FOR DOOR PANEL - ROCKWOOL INSULATION - MANUAL OPERATED RETRACTABLE TOP AND BOTTOM CRANKING SEAL - ROTATABLE TYPE END PANEL CLOSURE - PROVIDE STRUCTURAL SUPPORT FOR THE TRACKS COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE - 4mm X 76mm X 80mm HEAVY DUTY ALUMINUM TRACK AND HARD PLASTIC ROLLERS - 2 ROLLER PER PANEL CARRIER SYSTEM - SOSS HINGES FOR DOOR PANEL - ROCKWOOL INSULATION - MANUAL OPERATED RETRACTABLE TOP AND BOTTOM CRANKING SEAL - ROTATABLE TYPE END PANEL CLOSURE - PROVIDE STRUCTURAL SUPPORT FOR THE TRACKS COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE - 4mm X 76mm X 80mm HEAVY DUTY ALUMINUM TRACK AND HARD PLASTIC ROLLERS - 2 ROLLER PER PANEL CARRIER SYSTEM - SOSS HINGES FOR DOOR PANEL - ROCKWOOL INSULATION - MANUAL OPERATED RETRACTABLE TOP AND BOTTOM CRANKING SEAL - ROTATABLE TYPE END PANEL CLOSURE - PROVIDE STRUCTURAL SUPPORT FOR THE TRACKS COMPLETE WITH STANDARD PARTS AND ACCESSORIES. |
| JAMB/FRAME 1.50mm X 60mm POWDERCOATED ALUMINUM PROFILE AND 57mm POWDERCOATED ALUMINUM TOP AND BOTTOM CAPE BOARD | JAMB/FRAME 1.50mm X 60mm POWDERCOATED ALUMINUM PROFILE AND 57mm POWDERCOATED ALUMINUM TOP AND BOTTOM CAPE BOARD | JAMB/FRAME 1.50mm X 60mm POWDERCOATED ALUMINUM PROFILE AND 57mm POWDERCOATED ALUMINUM TOP AND BOTTOM CAPE BOARD | JAMB/FRAME 1.50mm X 60mm POWDERCOATED ALUMINUM PROFILE AND 57mm POWDERCOATED ALUMINUM TOP AND BOTTOM CAPE BOARD |
| NO. OF SETS 2 SETS | NO. OF SETS 1 SET | NO. OF SETS 1 SET | NO. OF SETS 1 SET |
| NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. |
| | | | |
| DOOR TAG (BD-05) | DOOR TAG (BD-06) | DOOR TAG (BD-07) | DOOR TAG (BD-08) |
| LOCATION 11TH FLOOR PANTRY AREA | LOCATION TYPICAL CONFERENCE ROOMS | LOCATION 18TH FLOOR MINI CONFERENCE ROOM | LOCATION 18TH FLOOR MINI CONFERENCE ROOM |
| DESCRIPTION 71mm THK OPERABLE WALL PANEL WITH 40 STC | DESCRIPTION 71mm THK OPERABLE WALL PANEL WITH 40 STC | DESCRIPTION 71mm THK OPERABLE WALL PANEL WITH 40 STC | DESCRIPTION 71mm THK OPERABLE WALL PANEL WITH 40 STC |
| FINISHES HIGH PRESSURE LAMINATE ON 6mm THK MARINE PLYWOOD BACKING | FINISHES HIGH PRESSURE LAMINATE ON 6mm THK MARINE PLYWOOD BACKING | FINISHES HIGH PRESSURE LAMINATE ON 6mm THK MARINE PLYWOOD BACKING | FINISHES HIGH PRESSURE LAMINATE ON 6mm THK MARINE PLYWOOD BACKING |
| HARDWARE - 4mm X 76mm X 80mm HEAVY DUTY ALUMINUM TRACK AND HARD PLASTIC ROLLERS - 2 ROLLER PER PANEL CARRIER SYSTEM - SOSS HINGES FOR DOOR PANEL - ROCKWOOL INSULATION - MANUAL OPERATED RETRACTABLE TOP AND BOTTOM CRANKING SEAL - ROTATABLE TYPE END PANEL CLOSURE - PROVIDE STRUCTURAL SUPPORT FOR THE TRACKS COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE - 4mm X 76mm X 80mm HEAVY DUTY ALUMINUM TRACK AND HARD PLASTIC ROLLERS - 2 ROLLER PER PANEL CARRIER SYSTEM - SOSS HINGES FOR DOOR PANEL - ROCKWOOL INSULATION - MANUAL OPERATED RETRACTABLE TOP AND BOTTOM CRANKING SEAL - ROTATABLE TYPE END PANEL CLOSURE - PROVIDE STRUCTURAL SUPPORT FOR THE TRACKS COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE - 4mm X 76mm X 80mm HEAVY DUTY ALUMINUM TRACK AND HARD PLASTIC ROLLERS - 2 ROLLER PER PANEL CARRIER SYSTEM - SOSS HINGES FOR DOOR PANEL - ROCKWOOL INSULATION - MANUAL OPERATED RETRACTABLE TOP AND BOTTOM CRANKING SEAL - ROTATABLE TYPE END PANEL CLOSURE - PROVIDE STRUCTURAL SUPPORT FOR THE TRACKS COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | HARDWARE - 4mm X 76mm X 80mm HEAVY DUTY ALUMINUM TRACK AND HARD PLASTIC ROLLERS - 2 ROLLER PER PANEL CARRIER SYSTEM - SOSS HINGES FOR DOOR PANEL - ROCKWOOL INSULATION - MANUAL OPERATED RETRACTABLE TOP AND BOTTOM CRANKING SEAL - ROTATABLE TYPE END PANEL CLOSURE - PROVIDE STRUCTURAL SUPPORT FOR THE TRACKS COMPLETE WITH STANDARD PARTS AND ACCESSORIES. |
| JAMB/FRAME 1.50mm X 60mm POWDERCOATED ALUMINUM PROFILE AND 57mm POWDERCOATED ALUMINUM TOP AND BOTTOM CAPE BOARD | JAMB/FRAME 1.50mm X 60mm POWDERCOATED ALUMINUM PROFILE AND 57mm POWDERCOATED ALUMINUM TOP AND BOTTOM CAPE BOARD | JAMB/FRAME 1.50mm X 60mm POWDERCOATED ALUMINUM PROFILE AND 57mm POWDERCOATED ALUMINUM TOP AND BOTTOM CAPE BOARD | JAMB/FRAME 1.50mm X 60mm POWDERCOATED ALUMINUM PROFILE AND 57mm POWDERCOATED ALUMINUM TOP AND BOTTOM CAPE BOARD |
| NO. OF SETS 2 SETS | NO. OF SETS 12 SETS | NO. OF SETS 1 SET | NO. OF SETS 1 SET |
| NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. |
| | | | |
| DOOR TAG (BD-09) | | | |
| LOCATION 24TH FLOOR FUNCTION ROOMS | | | |
| DESCRIPTION 71mm THK OPERABLE WALL PANEL WITH 40 STC | | | |
| FINISHES HIGH PRESSURE LAMINATE ON 6mm THK MARINE PLYWOOD BACKING | | | |
| HARDWARE - 4mm X 76mm X 80mm HEAVY DUTY ALUMINUM TRACK AND HARD PLASTIC ROLLERS - 2 ROLLER PER PANEL CARRIER SYSTEM - SOSS HINGES FOR DOOR PANEL - ROCKWOOL INSULATION - MANUAL OPERATED RETRACTABLE TOP AND BOTTOM CRANKING SEAL - ROTATABLE TYPE END PANEL CLOSURE - PROVIDE STRUCTURAL SUPPORT FOR THE TRACKS COMPLETE WITH STANDARD PARTS AND ACCESSORIES. | | | |
| JAMB/FRAME 1.50mm X 60mm POWDERCOATED ALUMINUM PROFILE AND 57mm POWDERCOATED ALUMINUM TOP AND BOTTOM CAPE BOARD | | | |
| NO. OF SETS 2 SETS | | | |
| NOTE SEE PROJECT MANUAL FOR ACCESSORIES AND SPECIFICATIONS DETAIL. | | | |

NOTE:
PURSUANT TO SECTION 4 OF ANNEX "A" OF THE REVISED IMPLEMENTING RULES AND REGULATIONS OF R.A. 5184, APPROVAL BY THE AUTHORIZED DPWH OFFICIALS OF DETAILED ENGINEERING SURVEYS AND DESIGN UNDERTAKEN BY CONSULTANTS NEITHER DIMINISHES THE RESPONSIBILITY OF THE LATTER FOR THE TECHNICAL INTEGRITY OF THE SURVEYS AND DESIGN NOR TRANSFER ANY PART OF THAT RESPONSIBILITY TO THE APPROVING OFFICIALS.

THE DESIGN CONSULTANT SHALL BE HELD RESPONSIBLE FOR THE FAILURE OF THE FACILITY/ES / STRUCTURES DUE TO FAULTY DESIGN EXCEPT FOR THE CHANGES MADE WITHOUT THE CONFORMITY OF THE CONSULTANTS.

DRAWINGS AND SPECIFICATIONS DULY SIGNED, STAMPED OR SEALED, AS INSTRUMENTS OF SERVICE ARE PROPERTY AND DOCUMENTS OF THE ARCHITECT, WHETHER THE OBJECT FOR WHICH THEY ARE MADE IS EXECUTED OR NOT. IT SHALL BE UNLAWFUL FOR ANY PERSON, WITHOUT THE WRITTEN CONSENT OF THE ARCHITECT OR AUTHOR OF SAID DOCUMENTS, TO DUPLICATE OR TO MAKE COPIES OF SAID DOCUMENTS FOR USE IN THE REPEITION OF AND FOR OTHER PROJECTS OR BUILDINGS, WHETHER EXECUTED PARTLY OR IN WHOLE.

SCHEDULE OF DOORS
SCALE: 1:50 M.