



REPUBLIC OF THE PHILIPPINES
PHILIPPINE STATISTICS AUTHORITY

REQUEST FOR QUOTATION

The **Philippine Statistics Authority (PSA)** through the Bids and Awards Committee (BAC), intends to procure Mirrorless Camera which shall be undertaken in accordance with Section 52.1 (b) (Shopping) of the 2016 Revised Implementing Rules and Regulations of Republic Act No. 9184, with an Approved Budget of the Contract (ABC) in the amount of **160,000.00** One Hundred Sixty Thousand Pesos Only

Please quote your **best offer** for the **item/s described herein**, subject to the Terms and Conditions provided below. Submit your quotation duly signed by you or your duly authorized representative **not later than** 12 3 NOV 2022 at 11:00Am through email at bac-secretariat@psa.gov.ph and bacsecretariat.psa@gmail.com.

For any clarification, you may contact us at telephone no. **(02) 8374-8263** or email address at gsdprocurement.psa@gmail.com

Minerva E. Esquivias
MINERVA ELOISA P. ESQUIVIAS
Chairperson, Bids and Awards Committee

TERMS AND CONDITIONS

- 1 Bidders shall provide correct and accurate information required in this form.
- 2 Price quotation/s must be valid for a period of **thirty (30) calendar days** from the date of submission.
- 3 Price quotation/s, to be denominated in Philippine peso, shall include all taxes, duties and/or levies payable.
- 4 Quotations exceeding the ABC shall be rejected.
- 5 Award of contract shall be made to the lowest quotation which complies with the technical specifications, and other terms and conditions stated herein. This procurement project is to be awarded by lot.
- 6 Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by you or your duly authorized representative.
- 7 In case of two or more bidders are determined to have submitted the LCRB, the PSA shall adopt and employ "draw lots" as the tie-breaking method to finally determine the single winning bidder in accordance with GPPB Circular 06-2005.
- 8 The item/s shall be delivered according to the requirements specified in the Purchase Request (PR).
- 9 The PSA shall have the right to inspect and/or test the goods to confirm their conformity to the Technical Specifications.
- 10 Payment shall be made after delivery and upon submission of the required supporting documents, i.e. Order Slip and/or Billing Statement, by the supplier. Our Government Servicing Bank, **Land Bank of the Philippines**, shall credit the amount due to the identified bank of the supplier **not earlier than twenty four (24) hours, but not later than forty eight (48) hours**, upon receipt of our advice. Please note that the corresponding **bank transfer fee**, if any, shall be chargeable to the account of the supplier.
- 11 Liquidated damages equivalent to one tenth (1/10) of one percent (1%) of the value of the goods not delivered within the prescribed period shall be imposed per day of delay. The PSA shall rescind the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies open to it.

Documents to be submitted	Deadline	Remarks
Copy of the 2022 Mayor's/Business Permit and valid PhilGEPS Registration	Not later than <u>12 3 NOV 2022</u> at <u>11:00Am</u> together with the quotation	In case not yet available, you may submit your expired Mayor's/Permit with Official Receipt of renewal application. However, a copy of your 2022 Mayor's/Business Permit shall be required to be submitted after award of contract but before payment .



Management System
ISO 9001:2015
www.tuv.com



PSA Complex, East Avenue, Diliman, Quezon City, Philippines 1101
Telephone: (632) 8938-5267
www.psa.gov.ph

RECEIVED
Jeremy
11/17/22

REQUEST FOR QUOTATION
PR No. 22-10-1668

After having carefully read and accepted the Terms and Conditions, I/We submit our quotation/s for the item/s as follows:

Item(s) and Specification(s), minimum	Unit	Quantity	Unit Price	Total Amount (VAT Inclusive)	Compliance with Technical Specifications (pls. check)	
					Yes	No
Mirrorless Camera for Community-Based Statistics Service						
Mirrorless Camera	unit	2				
<p>Specifications:</p> <p>Lens Mount: E-mount lenses Sensor Type: 35mm Sensor: 35mm full frame (35.8 x 23.9mm) Exmor CMOS sensor Number of Pixels: 24.7MP Anti-Dust System: Must have Anti-Dust System Image Quality Modes: RAW, RAW & JPEG, JPEG Extra fine, JPEG fine, JPEG Standard Video Recording: AVCHD 2.0 / MP4 / XAVC S (up to 1920 x 1080/60p 50Mbps Noise Reduction: Long exposure High ISO NR Multi Frame NR: Auto/ISO 100 to 51200</p>						
<p>AWB Micro Adjustmen: G7 to M7 (15 steps), A7 to B7 (15 steps) Bracketing: 3 Frames. H/L selectable White Balance Modes: Auto WB, Daylight, Shade, Cloudy, Incandescent, Flourescent (Warm White/Cool White/Day White/Daylight), Flash, Color Temperature (2500 to 9900 K) &Color Filter (G7 to M7: 15 steps, A7 to B7: 15 steps), Custom, Underwater</p>						
<p>Focus:</p> <p>Focus Type: Fast Hybrid AF (Phase-detection AF/contrast-detection AF) Focus Sensor: Exmor "CMOS sensor" Focus Point: 35mm full frame: 117 points (phase-detection AF) APS-C: 99 points (phase-detection AF) / 25 points (contrast-detection AF) Focus Sensitivity Range: EV-1 to EV20 (ISO100 equivalent with F2.0 lens attached) AF Mode: Singe-shot AF (AF-S), Continuous AF (AF-C), Direct Manual Focus (DMF), Manual Focus</p>						
<p>Focus Area: Wide (117 points (phase-detection AF), 25 points (contrast-detection AF)) Zone Center Flexible Spot (S/M/L) Loc-on AF (Wide/Zone/Center/Flexible Spot (S/M/L)) Type: Yes (with built-in LED type) AF Illuminator Range: Approx. 0.3m - Approx. 3.0m (with FE 28-70 mm F3.5-5.6 OSS attached)</p>						

<p>Exposure:</p> <p>Metering Type: 1200-zone evaluative metering Metering Sensor: Exmor "CMOS sensor" Metering Sensitivity: Ev-1 to EV20 (at ISO 100 equivalent with F2.0 lens attached) Metering Mode: Multi-segment, Center-weighted, Spot Exposure Modes: AUTO (iAUTO, Superior Auto), Programmed AE (P), Aperture priority (A), Shutter-speed priority (S), Manual (M), Scene Selection, Sweep Panorama, Movie Auto (AE) Bracketing: Cont./Bracket: Single, With 1/3 EV, 1/2 EV, 2/3 EV, 1.0 EV, 2.0 EV, 3.0 EV increments, 3/5 frames selectable ISO Sensitivity: ISO 50-25600 LCD Screen:</p> <p>Monitor Type: 3.0 in type TFT LCD Total Number of Dots: 1,228,800 dots Brightness Control (LCD): Manual (five steps between -2 and +2), Sunny Weather Mode Focus Magnifier: 35mm full frame: 5.9x, 11.7x, APS-C: 3.8x, 7.7x</p>						
<p>Shutter Speed: Still images: 1/8000 to 30sec., Bulb Movies: 1/8000 to 1/4 (1/3 step), Up to 1/60 in AUTO mode (up to 1/30 in Auto Slow Shutter Mode)</p> <p>Image Stabilization:</p> <p>Compensation Effect: 4.5 steps (based on CIPA standard. Pitch/yaw shake only. With Sonnar T* FE 55mm F1.8 ZA lens mounted, Long exposure NR off.)</p> <p>Drive:</p> <p>Drive modes: Single Shooting, Continuous shooting, Self-timer (10/2 sec. delay selectable), Self-timer (Cont.) (10 sec. delay 3/5 exposures selectable), Bracketing (Cont., Single, White Balance, DRO) Continuous Drive Speed (Approx. Max.): 5fps (in High Continuous Shooting)</p>						
<p>Playback:</p> <p>Playback Modes: Single (with or without shooting information Y RGB histogram & highlight/shadow warning) 9/25 frame index view Enlarged display mode (L: 18.8x, M: 12.3x, S: 9.4x, Panorama (Standard): 25.6x, Panorama (Wide): 38.8x, Auto Review (10/5/2) sec. Off) Image orientation (Auto/Manual/Off selectable) Slideshow Panorama scrolling Folder selection (Date/Still/MP4/AVCHD/XAVC S) Forward/Rewind (movie) Delete Protect</p> <p>Interface:</p> <p>PC Interface: Mass-storage, MTP, PC remote NFC: Must have NFC HD Output: HDMI micro connector (Type-D), BRAVIA Sync (link menu), PhotoTV HD, 4k still image playback Multi Interface Shoe: Must have Multi Interface Shoe Others: Microphone terminal (3.5mm Stereo minijack), Headphone Terminal (3.5mm Stereo minijack), Vertical Grip Connector Interfaces: 1. Headphone minijack; 2. Microphone miniack; 3. Multi/Micro USB Terminal; 4. Multi interface Shoe; 5. Vertical Grip Connector</p>						

<p>Audio:</p> <p>Microphone: Built-in stereo microphone or ECM-XYST1m/XLR-K1M (sold separately) Speaker: Must have Built-in, monaural</p> <p>Custom Functions:</p> <p>Custom Function Type: Custom key settings Programmable Setting</p> <p>Pwer:</p> <p>Supplied Battery: NP-FW50 W-Series Rechargeable Battery Pack Battery Life (still image): Up to 350 shots</p> <p>Size & Weight:</p> <p>External Power: AC Adapter AC-PW20 (optional) Dimensions (WxHxD): 126.9 x 95.7 x 59.7 mm Weight (with battery and memory card included): 556 g (Body Only)/ 599 g (With battery and media)</p>							
<p>WIFI:</p> <p>Wireless & Network Capabilities: 1. Downloadable Camera Apps; 2 One-Touch NFC Functionality; 3. Wi-Fi</p> <p>Other Features:</p> <p>Face Detection: On/Off (Regist. Faces)/Off Digital Zoom (still image): 35mm full frame: up to 8x APS-C: up to 8x Clear Image Zoom: Still/Movie: Approx. 2x Digital Zoom (Movie): 35mm full frame: Approx 4x. APS-C: Approx 4x. Lens Compensation: Peripheral shading, chromatic aberration, distortion</p>							
Total amount in words:							

Printed name of the authorized representative: _____ Signature: _____

Name of Company: _____ Position: _____

Address: _____ Email address: _____

Fax No.: _____ Tel. No.: _____ Mobile No.: _____

Date: _____