



**REQUEST FOR QUOTATION**

RFQ # 2020-09-217

16 September 2020

The Philippine Statistics Authority-Region 7 (PSA-R07) through its Bids and Awards Committee (BAC) will undertake Alternative Mode of Procurement, Small Value Procurement for the Procurement of CCTV Package and Wireless Microphone for 2020 ISSP- Office Productivity.

<b>Name of Project</b>	CCTV Package and Wireless Microphone for 2020 ISSP- Office Productivity
<b>Solicitation (If posted at the PhilGEPS)</b>	0700-2020-09-056
<b>Purchase Request No.</b>	0700-2020-08-042A
<b>Location</b>	PSA-RSSO 7, Gaisano South Bldg., Colon St., Cebu City
<b>Brief Description</b>	CCTV package and Wireless Microphone
<b>Quantity</b>	Please see page 3 of the RFQ for the detailed quantity
<b>Approved Budget for the Contract (ABC)</b>	Php85,000.00
<b>Contract Duration</b>	3-5 working days after the receipt of the Purchase Order
<b>Date of Delivery</b>	3-5 working days after the receipt of the Purchase Order

Please quote your **best price** on the item/s listed below and submit personally your **SEALED QUOTATION** not later than **22 September 2020, 5:00 P.M** through the address below, subject to the Terms and Conditions provided in this RFQ:

*Region 7 Bids and Awards Committee (R07 BAC)  
Philippine Statistics Authority – RSSO VII  
Gaisano Capital South Bldg, Colon St. Cebu City*

*Attn.: Mr. Caylord D. Niala/ Ms. Melita C. Jomoad/ Ms. Irish B. Velasco  
R07 BAC Secretariat  
Contact Nos.: (032)412-6794/254-0470 (telefax)  
Email address: psa07.rbac@gmail.com*

  
**EDWINA M. CARRIAGA**  
R07 BAC Chairperson

**Terms and Conditions:**

1. Only the suppliers registered at the Philippine Government Electronic Procurement System (PhilGEPS) shall be allowed to submit the quotation.
2. All entries must be typewritten/printed legibly in the Bid Form. Failure to use this form will result to disqualification of your bid.
3. Bidders shall provide correct and accurate information required in this form.
4. The bidder may quote for any or all lots and must quote all the items under a specific lot.
5. Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by you or your duly authorized representative/s.
6. Late submission of quotation shall not be accepted.
7. Bids exceeding the ABC for each item/lot shall be disqualified.

8. Award of contract shall be made to the Lowest Calculated and Responsive Bidder which complies with the specifications and other terms and conditions as stated herein.
9. The Lowest Calculated and Responsive Bidder shall be informed immediately.
10. In case of two or more bidders are determined to have submitted the Lowest Calculated Quotation / Lowest Calculated and Responsive Quotation, the PSA shall adopt and employ “*draw lots*” as the tie-breaking method to finally determine the single winning provider in accordance with GPPB Circular 06-2005.
11. The item/s shall be delivered according to the requirements specified in the Technical Specifications.
12. The PSA shall have the right to inspect and/or to test the goods to confirm their conformity to the technical specifications.
13. The following documentary requirements must be submitted prior to payment:
  - *Mayor’s/Business Permit*
  - *PhilGEPS Registration Number/Certificate*
  - *Income/Business Tax Return (for ABCs above P500K)*
  - *Omnibus Sworn Statement (for ABCs above P50K)*
14. The PSA reserves the right to reject any or all bid proposals, or declares the bidding a failure, or not to award the contract, and makes no assurance that a contract shall be entered into as a result of this invitation.
15. Mode of payment shall be made either through check or Advice to Debit Account (ADA) to the supplier.
16. Liquidated damages equivalent to one tenth of one percent (0.1%) of the value of the goods not delivered within the prescribed delivery period shall be imposed per day of delay. The PSA shall rescind the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies to it.

**BID FORM**

**IMPORTANT NOTES/INSTRUCTIONS:**

1. Make sure to read the Terms and Conditions stated in the Request for Quotation before filling out this form.
2. Use this form for your quotation. Additional bidder's proposal can also be attached to this form.
3. Ensure to indicate the price for the whole lot and the unit price per unit.
4. Ensure to fill-up the **TOTAL AMOUNT IN WORDS**.
5. Ensure to check the "Compliance with Technical Specifications" Column.
6. Submit your bid in any of the following:
  - a. Sealed in an envelope, or
  - b. Email to [psa07.rbac@gmail.com](mailto:psa07.rbac@gmail.com) only
7. Failure to follow these instructions will result to the disqualification of your entire quotation/bid.

Item No.	Item/s and specification/s (minimum)	Unit	Qty.	Approved Budget for the Contract (ABC) per unit	Unit Price (in Peso) Please indicate your offer/price here.	Total Amount (VAT inclusive)	Compliance with Technical Specifications (please check)	
							YES	NO
1	<b>CCTV Package</b>	set	2	30,000.00			( )	( )
	<b>Technical Specifications:</b> <ul style="list-style-type: none"> <li>• 1080p Turbo HD DVR</li> <li>• 1080p Full HD Dome Cameras with Metal Housing</li> <li>• 1080p Full HD Bullet Cameras with Metal Housing</li> <li>• Image Sensor: 2MP CMOS Image Sensor</li> <li>• Effective Pixels: 1920(H)*1080(V)</li> <li>• Shutter Time: 1/25(1/30) s to 1/50,000 s</li> <li>• Lens: Angle of View: 103°(2.8mm), 82.2°(3.6mm), 54°(6mm)</li> <li>• Lens Mount: M12</li> <li>• DVR Specs: H.264 &amp; Dual-stream video compression</li> <li>• DVR Specs: Support both HD-TVI and analog cameras with adaptive access</li> <li>• DVR Specs: Full channel@1800P resolution real-time recording</li> </ul>						( )	( )

	<ul style="list-style-type: none"> <li>DVR Specs: HDMI and VGA output at up to 1920×1080P resolution</li> <li>HDD: 1 TB;</li> <li>4 Channels;</li> </ul> <p><b>Note:</b> Includes full installation package (cables, connectors, and other materials needed to fully operate the units).</p>						( ) ( )	( ) ( )
2	<b>Wireless Microphone</b>	set	5	5,000.00			( ) ( )	( ) ( )
	<b>Specification:</b>						( ) ( )	( ) ( )
	Operating Range Under Typical Conditions:						( ) ( )	( ) ( )
	<ul style="list-style-type: none"> <li>100m (300ft)</li> </ul>						( ) ( )	( ) ( )
	<b>Audio Frequency Response (+/- 2dB)</b>						( ) ( )	( ) ( )
	<ul style="list-style-type: none"> <li>Minimum: 45Hz</li> <li>Maximum: 15kHz</li> </ul>						( ) ( )	( ) ( )
	<b>Total Harmonic Distortion (ref. +/- 38 kHz deviation, 1 kHz tone)</b>						( ) ( )	( ) ( )
	<ul style="list-style-type: none"> <li>0.5 %, typical</li> </ul>						( ) ( )	( ) ( )
	<b>Dynamic Range</b>						( ) ( )	( ) ( )
	<ul style="list-style-type: none"> <li>&gt;100dB A-weighted</li> </ul>						( ) ( )	( ) ( )
	<b>Operating Temperature Range</b>						( ) ( )	( ) ( )
	<ul style="list-style-type: none"> <li>-180 (0°F) to +50°C (+122°F)</li> </ul>						( ) ( )	( ) ( )
	<b>Transmitter Audio Polarity</b>						( ) ( )	( ) ( )
	<ul style="list-style-type: none"> <li>Positive pressure on microphone diaphragm (or positive voltage applied to tip of WA302 phone plug) produces positive voltage on pin 2 (with respect to pin 3 of low impedance output) and the tip of the high impedance 1/4-inch output.</li> </ul>						( ) ( )	( ) ( )
	<b>SLX 1 Handheld Transmitter Audio Input Level</b>						( ) ( )	( ) ( )
	<ul style="list-style-type: none"> <li>-10 dBV maximum at mic gain position</li> <li>+10 dBV maximum at 0 dB gain position</li> <li>+20 dBV maximum at -10 dB gain position</li> </ul>						( ) ( )	( ) ( )
	<b>Gain Adjustment Range</b>						( ) ( )	( ) ( )
	<ul style="list-style-type: none"> <li>30dB</li> </ul>						( ) ( )	( ) ( )
	<b>Input Impedance</b>						( ) ( )	( ) ( )
	<ul style="list-style-type: none"> <li>1 MΩ</li> </ul>						( ) ( )	( ) ( )
	<b>RF Transmitter Output</b>						( ) ( )	( ) ( )
	<ul style="list-style-type: none"> <li>30 mW maximum</li> </ul>						( ) ( )	( ) ( )

	<b>Dimension</b> <ul style="list-style-type: none"> <li>108mm H x 64 mm W x 19 mm D (4.25 x 2.50 x 0.75 in.)</li> </ul>								( )	( )
	<b>Weight</b> <ul style="list-style-type: none"> <li>81 grams (3 oz.) without batteries</li> </ul>								( )	( )
	<b>Housing</b> <ul style="list-style-type: none"> <li>Molded ABS case</li> </ul>								( )	( )
	<b>Power Requirements</b> <ul style="list-style-type: none"> <li>2 "AA" size alkaline or rechargeable batteries</li> </ul>								( )	( )
	<b>Battery Life</b> <ul style="list-style-type: none"> <li>&gt;8 hours (alkaline)</li> </ul>								( )	( )
	<b>SLX 2 Handheld Transmitter</b> <b>Audio Input Level</b> <ul style="list-style-type: none"> <li>+2 dBV maximum at -10dB position</li> <li>-8 dBV maximum at 0dB position</li> </ul>								( )	( )
	<b>Gain Adjustment Range</b> <ul style="list-style-type: none"> <li>10dB</li> </ul>								( )	( )
	<b>RF Transmitter Output</b> <ul style="list-style-type: none"> <li>30mW maximum</li> </ul>								( )	( )
	<b>Dimension (including SM58 cartridge)</b> <ul style="list-style-type: none"> <li>254 mm x 51 mm dia. (10 x 2 in.)</li> </ul>								( )	( )
	<b>Weight</b> <ul style="list-style-type: none"> <li>290 grams (10.2 oz) without batteries</li> </ul>								( )	( )
	<b>Housing</b> <ul style="list-style-type: none"> <li>Molded PC/ABS handle and battery cup</li> </ul>								( )	( )
	<b>Power Requirements</b> <ul style="list-style-type: none"> <li>2 "AA" size alkaline or rechargeable batteries</li> </ul>								( )	( )
	<b>Battery Life</b> <ul style="list-style-type: none"> <li>&gt;8 hours (alkaline)</li> </ul>								( )	( )
	<b>SLX 4 Receiver</b> <b>Dimension</b> <ul style="list-style-type: none"> <li>42 mm H x 197 mm W x 134 mm D (1.65 x 7.76 x 5.28 in.)</li> </ul>								( )	( )
	<b>Weight</b> <ul style="list-style-type: none"> <li>816g (1 lb. 13 oz)</li> </ul>								( )	( )
	<b>Housing</b> <ul style="list-style-type: none"> <li>Galvanized Steel</li> </ul>								( )	( )
	<b>Audio Output Level (ef. +/- 38kHz deviation with 1 kHz tone)</b> <ul style="list-style-type: none"> <li>XLR connector (into 600 Ω load): -13 dBV</li> <li>1/4-inch connector (into 3000 Ω load): -2 dBV</li> </ul>								( )	( )

<b>Output Impedence</b> • XLR connector: 200 Ω • 1/4-inch connector: 1kΩ						( )	( )
<b>XLR Output</b> • Impedance balanced Pin 1: Ground Pin 2: Audio Pin 3: No signal						( )	( )
<b>Sensitivity</b> • -105 dBm for 12 dB SINAD, typical						( )	( )
<b>Image Rejection</b> • >70 dB, typical						( )	( )
<b>Power Requirements</b> • 12-18 Vdc at 150 mA, supplied by external power supply						( )	( )
<b>Mode of Payment: SEND BILL Arrangement or 15-30 working days after receipt of the billing statement.</b>						( )	( )
<b>Price quotation/s validity: Must be valid for a period of thirty (30) calendar days from the date of submission.</b>						( )	( )
<b>TOTAL AMOUNT IN WORDS :</b> _____ _____							

Other Requirements:

After having carefully read and accepted your Terms and Conditions. I/We quote you on the item at prices noted above.

Printed Name of authorized representative/Signature \_\_\_\_\_

Position: \_\_\_\_\_

Name of Company \_\_\_\_\_

TIN #: \_\_\_\_\_ (Please specify if VAT or NON-VAT)

Address: \_\_\_\_\_ Email Address: \_\_\_\_\_

Fax No. \_\_\_\_\_ Tel No.: \_\_\_\_\_ Cellphone No. \_\_\_\_\_

Date: \_\_\_\_\_