



REQUEST FOR QUOTATION

RFQ # 2020-09-218

16 September 2020

The Philippine Statistics Authority-Region 7 (PSA-R07) through its Bids and Awards Committee (BAC) will undertake Alternative Mode of Procurement, Shopping for the Supply and Delivery of IT Equipment's and Audio and Visual Equipment for 2020 ISSP-Office Productivity.

Name of Project	IT Equipment and Audio and Visual Equipment for 2020 ISSP- Office Productivity
Solicitation (If posted at the PhilGEPS)	0700-2020-09-057
Purchase Request No.	0700-2020-08-042A
Location	PSA-RSSO 7, Gaisano South Bldg., Colon St., Cebu City
Brief Description	Category A - IT Equipment's for 2020 ISSP- Office Productivity
Quantity	Please see page 3 of the RFQ for the detailed quantity
Approved Budget for the Contract (ABC)	Php768,600.00
Contract Duration	3-5 working days after the receipt of the Purchase Order
Date of Delivery	3-5 working days after the receipt of the Purchase Order

Please quote your **best price** on the item/s listed below and submit personally your **SEALED QUOTATION** not later than **22 September 2020, 5:00 P.M** through the address below, subject to the Terms and Conditions provided in this RFQ:

Region 7 Bids and Awards Committee (R07 BAC)
Philippine Statistics Authority – RSSO VII
Gaisano Capital South Bldg, Colon St. Cebu City

Attn.: Mr. Cayylord D. Niala/ Ms. Melita C. Jomud/ Ms. Irish B. Velasco
R07 BAC Secretariat
Contact Nos.: (032)412-6794/254-0470 (telefax)
Email address: psa07.rbac@gmail.com


EDWINA M. CARRIAGA
R07 BAC Chairperson

Terms and Conditions:

1. Only the suppliers registered at the Philippine Government Electronic Procurement System (PhilGEPS) shall be allowed to submit the quotation.
2. All entries must be typewritten/printed legibly in the Bid Form. Failure to use this form will result to disqualification of your bid.
3. Bidders shall provide correct and accurate information required in this form.
4. The bidder may quote for any or all lots and must quote all the items under a specific lot.
5. Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by you or your duly authorized representative/s.
6. Late submission of quotation shall not be accepted.
7. Bids exceeding the ABC for each item/lot shall be disqualified.

8. Award of contract shall be made to the Lowest Calculated and Responsive Bidder which complies with the specifications and other terms and conditions as stated herein.
9. The Lowest Calculated and Responsive Bidder shall be informed immediately.
10. In case of two or more bidders are determined to have submitted the Lowest Calculated Quotation / Lowest Calculated and Responsive Quotation, the PSA shall adopt and employ *“draw lots”* as the tie-breaking method to finally determine the single winning provider in accordance with GPPB Circular 06-2005.
11. The item/s shall be delivered according to the requirements specified in the Technical Specifications.
12. The PSA shall have the right to inspect and/or to test the goods to confirm their conformity to the technical specifications.
13. The following documentary requirements must be submitted prior to payment:
 - *Mayor's/Business Permit*
 - *PhilGEPS Registration Number/Certificate*
14. The PSA reserves the right to reject any or all bid proposals, or declares the bidding a failure, or not to award the contract, and makes no assurance that a contract shall be entered into as a result of this invitation.
15. Mode of payment shall be made either through check or Advice to Debit Account (ADA) to the supplier.
16. Liquidated damages equivalent to one tenth of one percent (0.1%) of the value of the goods not delivered within the prescribed delivery period shall be imposed per day of delay. The PSA shall rescind the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies to it.

BID FORM

IMPORTANT NOTES/INSTRUCTIONS:

1. Make sure to read the Terms and Conditions stated in the Request for Quotation before filling out this form.
2. Use this form for your quotation. Additional bidder's proposal can also be attached to this form.
3. Ensure to indicate the price for the whole lot and the unit price per unit.
4. Ensure to fill-up the **TOTAL AMOUNT IN WORDS**.
5. Ensure to check the "Compliance with Technical Specifications" Column.
6. Submit your bid in any of the following:
 - a. Sealed in an envelope, or
 - b. Email to psa07.rbac@gmail.com only
7. Failure to follow these instructions will result to the disqualification of your entire quotation/bid.

Item No.	Item/s and specification/s (minimum)	Unit	Qty	Approved Budget for the Contract (ABC) per unit	Unit Price (in Peso) Please indicate your offer/price here.	Total Amount (VAT inclusive)	Compliance with Technical Specifications (please check)	
							YES	NO
1	CATEGORY A IT Equipment's for 2020 ISSP Office Productivity	Lot	1	768,600.00			()	()
1.1	LED Projector (HDMI Ready)	unit	5	39,000.00			()	()
	Specification: 5 units @ PHP 39,000/unit Optical <ul style="list-style-type: none"> • LCD Panel: 0.63" (1.6cm) P-Si TFT x 3 • Resolution: XGA (1024x768) • White light output (brightness): 4000 ANSI Lumens (Normal Mode); 2600 ANSI Lumens (Eco Mode) • Brightness: 4000 ANSI Lumens (Normal Mode); 2600 ANSI Lumens (Eco Mode) • Contrast Ratio: 3000:01:00 • Lens: Manual Focus, Manual Zoom x 1.2 • Lamp Wattage: 215 W UHP • Lamp Life: 5000 hours (Normal Mode); 6000 hours (Eco Mode)* 						()	()

<p>blackboard, whiteboard greenboard, photo), Daytime Mode, Input Source Naming (English), Resolution setting, Template, Closed Caption (for NTSC & component 480i only), Audio pass through, Framelock, Audio ports assign, Cloning, Drawing function (Optional wireless pen tablet TB-1 is necessary), Eco Mode (Normal, Eco, Intelligent Eco, Saver), iOS Connectivity</p>								
<ul style="list-style-type: none"> • Outward: Easy lamp replace from top, Air filter slides towards front side or top 							()	()
<ul style="list-style-type: none"> • Power on & off: Direct on, Auto off 							()	()
<ul style="list-style-type: none"> • Security Systems: Security bar, PIN-Lock, MyScreen Password, Keypad-Lock, Kensington slot, Transition detector, My Text, Security label 							()	()
<ul style="list-style-type: none"> • Network: Network presentation (PC still/moving picture transfer), Campus Notification System, Configure and control projector via web browser, receive alerts via e-mail, projector management via SNMP, Crestron RoomView®, Scheduling, My Image, displaying text data transferred via the network, Command Control via network, A MX Device Discovery, PJ Link™, Network Bridge 							()	()
Connections								
<ul style="list-style-type: none"> • Digital Input: 1 x HDMI (HDCP compatible) 							()	()
<ul style="list-style-type: none"> • Computer Input: 2 x 15-pin Mini D-sub 							()	()
<ul style="list-style-type: none"> • Monitor output: 1 x 15-pin Mini D-sub (RCA combination) 							()	()
<ul style="list-style-type: none"> • Video Input: 2 x 15-pin Mini D-sub (shared with analogue computer in 1/2); 1 x RCA for composite; 1 x Mini-DIN for S-Video 							()	()
<ul style="list-style-type: none"> • Audio Input: 2 x Stereo Mini Jack; 1 x pair RCA (L/R); 1 x Microphone Jack (Stereo Mini) 							()	()
<ul style="list-style-type: none"> • Audio Output: 1 x pair RCA (L/R) 							()	()
<ul style="list-style-type: none"> • USB Type A: 2 x USB Type A (for PC-less presentation and wireless network) 							()	()

	<ul style="list-style-type: none"> • USB Type B: 1 x USB Type B (for USB display or USB mouse control) • Wired network: 1 x RJ-45 • Wireless network: Option, IEEE802.11b/g/n ready (optional wireless adapter required) • Control: 1 x 9-pin D-sub for RS232C Control 						()	()
							()	()
							()	()
							()	()
	Power							
	<ul style="list-style-type: none"> • Power Supply: 100-120V / 220-240V auto switching • Power Consumption/Standby: 300W/<0.5W (AC 220-240V) 						()	()
							()	()
	Physical							
	<ul style="list-style-type: none"> • Dimensions (W x H x D) • (Without feet): 317x98x288mm (excluding feet and extrusions) • Weight: 3.6kg • Noise Level: 35dB (Normal Mode)/31dB (Eco mode) • Air Filter: Hybrid (up to 5000 hours) 						()	()
							()	()
							()	()
							()	()
							()	()
	Miscellaneous							
	<ul style="list-style-type: none"> • MISCELLANEOUS: Indicator lights (lamp, temp, power), Ceiling mount image, Rear projection image, Serial number label on side, MAC PC support: PJ Control software, MAC address label on side, LiveViewer software 						()	()
							()	()
							()	()
	Certification							
	<ul style="list-style-type: none"> • CERTIFICATION: UL60950-1/cUL, FCC Part 15 subpart B class B, CE Marking: EN61000-3-2, EN61000-3-3, EN55022, EN55024 (EMC Directive), 						()	()
	EN60950-1 (Low voltage directive), WEEE, RoHS, ErP (lot6) compliant, DEMKO-GS, GOST-R							
	Accessories Supplied							
	<ul style="list-style-type: none"> • ACCESSORIES SUPPLIED: Remote control with batteries (HL02881), Computer cable, Power cord, Lens cap, Security label, Adapter cover, User manual (detail & concise), Network & wireless software (CD-ROM) 						()	()
							()	()
	Warranty: 2 years warranty							

1.2	HDMI to HDMI Cable 5M Specification: 22 units @ PHP 800/unit In-wall- Series Fire resistant PVC jacket <ul style="list-style-type: none"> • Supports Latest HDMI Standard: 4k,UHD,3D,Audio Return Channe (ARC), Category 2 Certified, 18Gpbs/600MHz Refresh Rate, 2160p,1080p, 48 it Deep Color, Ethernet backward compatible with earlier version • 100% Pure copper conductors, Triple Cable Shielding, 24K Gold-plated full metal jacket connectors • Compatible with all HDMI Components: connects Blu-Ray Player, Apple TV, Xbox One, PS4,Roku, laptops with HDMI output to 4K, UHD TV, Projectors • A/V Receiver 	unit	22	800.00			() ()	() ()
1.3	VGA Cable (10 Meters) Specification: 16 units @ PHP 500/unit <ul style="list-style-type: none"> • Heavy duty SVGA monitor cord M/M with A1-foil shielding and dual cores protect againts EMI/RFI interference • Nickel-plated connectors • Inner condulnner conductor: 3 x coax (RGB) + 6 sync lines for high quality video signal transmission • D-sub male to male plug VGA extension cable ends screw-in to ensure strong connection 	unit	16	500.00			() ()	() ()
1.4	External Hard Drive Specification: 56 units @ PHP 5,000/unit <ul style="list-style-type: none"> • Storage Capacity: 2 TB • Connection: USB 3.0 • Hard Drive Size: 2.5 inches • Item Size (L*W*H): 4.60 x 3.14 x 0.58 inches 	unit	56	5,000.00			() ()	() ()
							() ()	() ()
							() ()	() ()
							() ()	() ()
							() ()	() ()

	<ul style="list-style-type: none"> • Package Size: (L*W*H): 5.70 x 4.13 x 1.25 inches • Package Weight: 207 grams 						()	()
1.5	Mouse	unit	50	950.00			()	()
	Specification: 50 units @ PHP 950/unit <ul style="list-style-type: none"> • Connection Type: 2.4GHz wireless connection • Wireless Range: 33 Feet (10 meters) • Connect /Power: Yes. On/off switch Battery Details: <ul style="list-style-type: none"> • Battery Type: 1 x AA • Battery Life (not rechargeable): 24 months • DPI (Min/Max): 1000± • Sensor Technology: Yes, 2D, mechanical • Sensor Resolution: 1000dpi • Scrool Wheels: Yes • Number of Buttons: 3 • Standard and Special buttons: Middle Click System Requirements: <ul style="list-style-type: none"> • Windows 10 or later, Windows 7, Windows 8 • Window RT, Mac OSX 10.5 or later, Chrome OS, Linux Kernel 2.6+2" • Interface: USB 						()	()
1.6	UPS for Workstation	unit	41	4,500.00			()	()
	Specification: 41 units @ PHP 4,500/unit Output <ul style="list-style-type: none"> ✓ "Output Power Capacity 500 Watts / 625 VA" 						()	()

✓	"Max Configurable Power 500 Watts / 0 VA"						()	()
✓	"Nominal Output Voltage 230 V"						()	()
✓	"Efficiency at Full Load 65.3%"						()	()
✓	"Topology Standby"						()	()
✓	"Waveform Type Square wave"						()	()
✓	"Output Connectios (3) Universal Receptacle (Battery Backup)"						()	()
✓	"Efficiency at Half Load 75.8%"						()	()
Input								
✓	"Nominal Input Voltage 230 V"						()	()
✓	"Input Frequency 45 - 65 Hz"						()	()
✓	"Input Connections IEC-320 C14"						()	()
✓	"Cord Length 1.22 meters"						()	()
✓	"Input voltage range for main operations 151 - 299V"						()	()
✓	"maximum Input Current 3A"						()	()
✓	"Type of input Protection 3-pole breaker"						()	()
✓	"battery Type maintenance free sealed lead- Acid Battery with suspended"						()	()
✓	"Included Battery modules 1"						()	()
✓	"Typical recharge time 6 hour(s)"						()	()
Surge Protection and Filtering								
✓	"Surge energy rating 273 Joules"						()	()
Environmental								
✓	"Operating Environmental 0-40 0C"						()	()
✓	"Operating Relative Humidity 0 - 95%"						()	()
✓	"Storage Temperature -15 - 400C "						()	()
✓	"Storage Relative Humidity 0 - 95%"						()	()

	<ul style="list-style-type: none"> ✓ Audible noise at 1 meter from surface of unit 45.00dBA <p>Conformance</p> <ul style="list-style-type: none"> ✓ "Standard Warranty 2 years repair or Replace" <p>Sustainable offer Status RoHS"</p> <ul style="list-style-type: none"> ✓ "RoHS ✓ Compliant" 						()	()
1.7	Wireless Router	unit	6	6,000.00			()	()
	<p>Specifications</p> <p>6 units @ PHP 6,000/unit</p> <ul style="list-style-type: none"> • Standards: IEEE 802.11ax/ac/n/a 5 GHz IEEE 802.11n/b/g 2.4 GHz" • Wifi Speeds: 5 GHz: 1201 Mbps (802.11ax) • 2.4 GHz: 300 Mbps (802.11n) • Wifi Range: 4× Fixed High- Performance Antennas • Multiple antennas form a signal- boosting array to cover more directions and large areas • Beamforming • Concentrates wireless signal strength towards clients to expand WiFi range • Wifi Capacity: Dual-Band Allocate devices to different bands for optimal performance • OFDMA Simultaneously communicates with multiple Wi-Fi 6 clients • Airtime Fairness Improves network efficiency by limiting excessive occupation • 4 Streams • Connect your devices to more bandwidth • Working Modes: Router Mode Access Point Mode • Processor: 1.5 GHz Triple-Core CPU • Ethernet Ports: 1 x Gigabit WAN port; 4 x Gigabit LAN ports • Buttons: WPS/Wi-Fi Button Power On/Off Button 						()	()

• LED On/Off Button							()	()
• Reset Button							()	()
• Power: 12 V – 1 A							()	()
• WiFi Encryption: WEP							()	()
• WPA							()	()
• WPA2							()	()
• WPA/WPA2-Enterprise (802.1x)							()	()
• Network Security: SPI Firewall							()	()
• Access Control							()	()
• IP & MAC Binding							()	()
• Application Layer Gateway							()	()
• Guest Network: 1× 5 GHz Guest Network 1× 2.4 GHz Guest Network							()	()
• VPN Server: Open VPN; PPTP							()	()
• Protocols: IPv4; IPv6							()	()
• Parental Controls: URL Filtering; Time Controls							()	()
• WAN Type: Dynamic IP							()	()
• Static IP							()	()
• PPPoE							()	()
• PPTP							()	()
• L2TP							()	()
• Quality of Service: QoS by Device							()	()
• NAT Forwarding: Port Forwarding							()	()
• Port Triggering							()	()
• DMZ							()	()
• UPnP							()	()
• IPTV: IGMP Proxy							()	()
• IGMP Snooping							()	()
• Bridge							()	()
• Tag VLAN							()	()
• DHCP: Address Reservation							()	()
• DHCP Client List							()	()
• Server							()	()
• Management: Tether App; Webpage							()	()

	<ul style="list-style-type: none"> Package Contents: Wi-Fi Router; Power Adapter; RJ45 Ethernet Cable; Quick Installation Guide 						()	()
	Mode of Payment: SEND BILL Arrangement or 15-30 working days after receipt of the billing statement.						()	()
	Price quotation/s validity: Must be valid for a period of thirty (30) calendar days from the date of submission.						()	()
	TOTAL AMOUNT IN WORDS : <hr/> <hr/>							

Other Requirements:

After having carefully read and accepted your Terms and Conditions. I/We quote you on the item at prices noted above.

Printed Name of authorized representative/Signature _____

Position: _____

Name of Company _____

TIN #: _____ (Please specify if **VAT** or **NON-VAT**)

Address: _____ Email Address: _____

Fax No. _____ Tel No.: _____ Cellphone No. _____

Date: _____