

| Item/s and specification/s (minimum)  | Unit | Qty. | Unit Price | Total Amount<br>(VAT inclusive) | Compliance with<br>Technical Specifications<br>(Please check) |    |
|---|------|------|------------|---------------------------------|---|----|
|   |      |      |            |                                 | YES   | NO |
| Min Document Size 89 x 127 mm (Simplex), 89 x 170 mm (Duplex)<br>Max Document Size: 215.9 x 3048 mm<br>Support Paper Thickness 50gsm - 120 gsm<br>ADF Capacity 50 sheets<br>Automatic Duplex Scanning Yes(3-pass)<br>Daily Duty Cycle: Up to 1500 pages / day   |      |      |            |                                 |   |    |
| <b>LOT 8</b><br><b>UPS FOR WORKSTATION</b><br>Specification:<br>Output:<br><i>Output Power Capacity</i> 325 Watts / 625 VA<br><i>Max Configurable Power</i> 325 Watts / 0 VA<br><i>Nominal Output Voltage</i> 230 V<br><i>Efficiency at Full Load</i> 65.3%<br><i>Topology</i> Standby<br><i>Waveform Type</i> Square wave<br><i>Output Connections</i> (3) Universal Receptacle (Battery Backup)<br><i>Efficiency at Half Load</i> 75.8%<br>Input:<br><i>Nominal Input Voltage</i> 230 V<br><i>Input Frequency</i> 45 - 65 Hz<br><i>Input Connections</i> IEC-320 C14<br><i>Cord Length</i> 1.22 meters<br><i>Input voltage range for main operations</i> 151 - 299V<br>maximum Input Current 3A<br><i>Type of input Protection</i> 3-pole breaker<br><i>battery Type</i> maintenance free sealed lead-Acid Battery with suspended<br>Included Battery modules 1<br><i>Typical recharge time</i> 6 hour(s)<br>Surge Protection and Filtering<br><i>Surge energy rating</i> 273 Joules<br>Environmental<br><i>Operating Environmental</i><br><i>Operating Relative Humidity</i><br><i>Storage Temperature</i><br><i>Storage Relative Humidity</i><br><i>Audible noise at 1 meter from</i><br>Conformance:<br><i>Standard Warranty</i><br>Sustainable Status:<br><i>RoHS Compliant</i> | pcs  | 28   | P_____     | P_____                          |   |    |
| <b>LOT 9</b><br><b>VGA Cable 10m</b><br>Specification:<br>Heavy duty SVGA monitor cord M/M with A1-foil shielding and dual cores<br>protect againsts EMI/RFI interference<br>Nickel-plated connectors<br>Inner conductor: 3 x coax (RGB) + 6 sync lines for high quality video<br>signal transmission<br>D-sub male to male plug VGA extension cable ends screw-in to ensure strong<br>connection   | pcs  | 17   | P_____     | P_____                          |   |    |
| <b>LOT 10</b><br><b>Mouse (Wireless)</b><br>Specification<br>Connection Type: 2.4GHz wireless connection<br>Wireless Range: 33 Feet (10 meters)<br>Connect /Power: Yes. On/off switch<br>Battery Details:<br>Battery Type: 1 x AA<br>Battery Life (not rechargeable): 24 months<br>DPI (Min/Max)" 1000±<br>Sensor Technology: Yes, 2D, mechanical<br>Sensor Resolution: 1000dpi<br>Scroll Wheels: Yes<br>Number of Buttons: 3<br>Standard and Special buttons: Middle Click<br>System Requirements:<br>Windows 10 or later, Windows 7, Windows 8<br>Window RT, Mac OSX 10.5 or later, Chrome OS, Linux Kernel 2.6+2<br>Interface: USB   | pcs  | 134  | P_____     | P_____                          |   |    |

| Item/s and specification/s (minimum) | Unit | Qty. | Unit Price | Total Amount<br>(VAT inclusive) | Compliance with<br>Technical Specifications<br>(Please check) |    |
|--------------------------------------|------|------|------------|---------------------------------|---|----|
|                                      |      |      |            |                                 | YES   | NO |
| TOTAL AMOUNT IN FIGURES:             |      |      |            | P                               |   |    |
| TOTAL AMOUNT IN WORDS:               |      |      |            |                                 |   |    |

Other Requirements:

After having carefully read and accepted your Terms and Conditions. I/We quote you on the item at prices noted above.

Printed Name of authorized representative/Signature: \_\_\_\_\_

Position: \_\_\_\_\_

Name of Company: \_\_\_\_\_

Address: \_\_\_\_\_ EmailAddress: \_\_\_\_\_

Fax No. \_\_\_\_\_ Tel No. \_\_\_\_\_ Cellphone No. \_\_\_\_\_

Date: \_\_\_\_\_