



REPUBLIC OF THE PHILIPPINES
PHILIPPINE STATISTICS AUTHORITY

REQUEST FOR QUOTATION

The **Philippine Statistics Authority (PSA)** through the Bids and Awards Committee (BAC), intends to

procure Procurement of Portable Sound System
 which shall be undertaken in accordance with Section 52.1 (Shopping)
 of the 2016 Revised Implementing Rules and Regulations of Republic Act No. 9184, with an Approved Budget of the
 Contract (ABC) in the amount of 889,200.00 *Eight Hundred Eighty Nine Thousand Two Hundred Pesos Only.*

Please quote your **best offer** for the **item/s described herein**, subject to the Terms and Conditions provided
 below. Submit your quotation duly signed by you or your duly authorized representative **not later than**
JUNE 21, 2018 at 11:00 AM through email at bac-secretariat@psa.gov.ph

For any clarification, you may contact us at telephone no. **(02) 8374-8263** or email address at
gsdprocurement.psa@gmail.com

Minerva Esquivias
MINERVA ELOISA P. ESQUIVIAS

Chairperson, Bids and Awards Committee

TERMS AND CONDITIONS

- 1 Bidders shall provide correct and accurate information required in this form.
- 2 Price quotation/s must be valid for a period of **thirty (30) calendar days** from the date of submission.
- 3 Price quotation/s, to be denominated in Philippine peso, shall include all taxes, duties and/or levies payable.
- 4 Quotations exceeding the ABC shall be rejected.
- 5 Award of contract shall be made to the lowest calculated and responsive bid (LCRB).
- 6 Any interlineations, erasures or overwriting shall be valid only if they are signed or initialed by you or your duly authorized representative.
- 7 In case of two or more bidders are determined to have submitted the LCRB, the PSA shall adopt and employ "draw lots" as the tie-breaking method to finally determine the single winning bidder in accordance with GPPB Circular 06-2005.
- 8 The item/s shall be delivered according to the requirements specified in the Purchase Request (PR).
- 9 The PSA shall have the right to inspect and/or test the goods to confirm their conformity to the Technical Specifications.
- 10 Payment shall be made after delivery and upon submission of the required supporting documents, i.e. Order Slip and/or Billing Statement, by the supplier. Our Government Servicing Bank, **Land Bank of the Philippines**, shall credit the amount due to the identified bank of the supplier **not earlier than twenty four (24) hours, but not later than forty eight (48) hours**, upon receipt of our advice. Please note that the corresponding **bank transfer fee**, if any, shall be chargeable to the account of the supplier.
- 11 Liquidated damages equivalent to one tenth (1/10) of one percent (1%) of the value of the goods not delivered within the prescribed period shall be imposed per day of delay. The PSA shall rescind the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies open to it.

Documents to be submitted	Deadline	Remarks
Copy of the 2023 Mayor's/Business Permit and valid PhilGEPS Registration	Not later than <u>6/22/18</u> at <u>11:00AM</u>	Together with quotation.



Management System
 ISO 9001:2015



PSA Complex, East Avenue, Diliman, Quezon City, Philippines 1101
 Telephone: (632) 8938-5267
 www.psa.gov.ph

RECEIVED
 GSD Procurement
 Name: Dne
 Date: 6/8
 Time: 10:30 AM

REQUEST FOR QUOTATION

PR No. 23-06-0605

After having carefully read and accepted the Terms and Conditions, I/We submit our quotation/s for the item/s as follows:

Item(s) and Specification(s), minimum	Unit	Quantity	Unit Price	Total Amount (VAT Inclusive)	Compliance with Technical Specifications (pls. check)	
					Yes	No
Procurement of Portable Sound System	Lot	1				
I. Must include 6 set of Portable Public Address (PA) System						
II. Must include 6 set Wireless Dual Vocal System with Two Handheld Transmitter Microphone						
III. Must include 2 set of Wireless Dual Presenter System with Two Lavalier Microphone						
Technical Specification for Portable Public Address (PA) System						
1. Must be System Type Powered mixer with 2 passive speakers Powered Mixer						
2. Must have 10-channel mixer (4 mono/line + 6 mono/ 3 stereo line)						
3. Must have Bluetooth Ver 4.1, A2DP v1.2 and Approximately 10m for bluetooth range						
4. Must have 3-band (HIGH shelving: 8kHz, MID peaking: 2.5kHz, LOW Shelving: 100Hz) for Channe; EQ						
5. Must have Hi-Z switch: CH4, ST/MONO switch: CH5/6-9/10 for channel functions						
6. Must have SPX Digital Reverb (4 program, parameter control for Digital Effects)						
7. Must have Feedback suppressor, 1-Knob Master EQ for Output processing						
8. Must have +30V (CH1,2) for Phantom Power						
9. Must have speakers Out (L,R), Monitor Out (L/MONO,R), Subwoofer Out (Mono) with Auto HPF for outputs						
10. Must have Reverb foot switch						
11. Must have built in amplifiers (680W (340W+340W) power output						
12. Must have Two-way bass-reflex speaker for speaker type(LF:10" woofer/HF:1.4" voice coil compression driver)						
13. Must have top handle						
14. Must have 34.8-35.2mm pole socket for the pole socket						
Included Accessories						
15. Must have cover panel, Power cord (2m), speaker cables (6m) x 2, Non-skid pads x12						
16. Must have 1-year warranty for parts and services						

Wireless Dual Vocal System with Two Handheld Transmitter Microphone						
Wireless Handheld Transmitter Microphone Technical Specification						
1. Must have Two handheld wireless transmitter microphone per set						
2. Must be Dynamic type microphone						
3. Must be Cardioid for Polar Pattern						
4. Must have Operating range of 300ft (91m) line of sight						
5. Must have Available frequencies between 524-865 MHz						
6. Must have Audio Range 60-15,000 Hz						
7. Must have Transmitter RF Output Power 10 mW, Typical						
8. Must have Audio Output Connector XLR and 1/4 (6.3mm) unbalanced						
9. Must have Maximum Output Level of -27 dBV (XLR, mic level), -13 dBV (1/4")						
10. Must have Dynamic Range of 100 dB A-weighted						
11. Must have System Distortion of 0.5% THD typical (ref. +/-38 kHz deviation, 1 kHz tone)						
Dual Wireless Diversity Receiver						
Technical Specification						
12. Must have Dual wireless diversity receiver compatible with Two wireless handheld transmitter microphone per set						
13. Must have 75m (250ft) (Line of Sight) for Hi power mode and 18m (60ft) (Line of Sight) for LO power mode						
14. Must have FM, Ref±48 kHz deviation with 1 kHz tone for Modulation						
15. Must have <0.5% for Total Harmonic Distortion						
16. Must have 90 dB, A-weighted, typical for Dynamic Range						
17. Must have Molded ABS for the Housing						
Audio Output Level						
(Ref. ±48kHz deviation with 1 kHz tone						
18. Must have -16 dBv for XLR connector into 100 kΩ						
19. Must have -22 dBV for 6.35mm(1/4") connector into 100Ω load						
J9 Audio Output Level						

20. Must have -21 dBV XLR connector into 100Ω load						
21. Must have -27 dBV for 6.35mm (1/4") connector into 100 Ω load						
Output Impedance						
22. Must have 600Ω for the XLR connector						
23. Must have 600 Ω for 6.35 mm (1/4") connector						
Sensitivity						
24. Must have - 105 dBm for 12 dB SINAD, typical						
Warranty						
25. Must have 1-year warranty for parts and services						
Wireless Dual Presenter System with Two Lavalier Microphones						
Lavalier Microphone						
Technical Specification						
1. Must have Two Lavalier Condenser Microphone per set						
2. Must have Two Wireless bodypack transmitter compatible with Lavalier Microphone per set						
3. Must be clip-on cardioid condenser microphone						
4. Must be Electret Condenser Type						
5. Must have Frequency Response 50 to 20,000 Hz						
6. Must be Polar Pattern Unidirectional (Cardioid)						
7. Must have Output Impedance of 600Ω						
8. Must have Audio Output Level -43.5 dBV/Pa						
9. Must have Signal-To-Noise Ratio @ 1 kHz of 72 dB						
10. Must have Maximum SPL 1000Ω load, @ 3 % THD of 139.0 dB						
11. Must have Dynamic Range @ 1 kHz, 1000 Ω of 117.0 dB						
12. Must have Equivalent Output Noise Typical, A-Weighted of 22 dB"						
13. Must have Cable with 1.3m (50 in.)						
14. Must have TA4F Connector						

Wireless Bodypack Transmitter						
Technical Specification						
15. Must have Power and battery status LED						
16. Must have Adjustable gain control						
17. Must have Quick & easy frequency matching						
18. Must have 300 feet (91 m) operating range (line of sight)						
Dual Wireless Receiver						
Technical Specification						
19. Must have Dual Wireless receiver compatible with Two Lavalier Condenser Microphone bodypack transmitter per set						
20. Must have microprocessor-controlled internal antenna diversity						
21. Must have One-touch quick scan frequency selection for the Dual Wireless Receiver						
22. Must have 1/4" and XLR audio outputs						
23. Must have Two color audio status indicator led						
Warranty						
24. Must have 1-year warranty for parts and services						

Printed name of the authorized representative: _____ Signature: _____

Name of Company: _____

Address: _____ Email address: _____

Fax No.: _____ Tel. No.: _____ Mobile No.: _____

Date: _____