

Republic of the Philippines PHILIPPINE STATISTICS AUTHORITY

| Reference No. 16BAC00 | · | | |
|-----------------------|--------------|--------------|---------|
| 7 September 2016 | | | |
| SUBJECT: | SUPPLEMENTAL | BID BULLETIN | N NO. 1 |
| | | | |

This serves as the official transmittal of Bid Bulletin No. 1 for the Procurement for the Supply and Delivery of Rackmount Server. This bulletin is being issued to amend the Bidding Documents and clarify queries from prospective bidders.

Please be informed that the contents of the Bidding Documents that have not been modified shall remain in full force and effect.

The bulletin shall be posted on both the PhilGEPS and PSA website.

Truly yours,

JOSEPH P. CAJITA
BAC Secretariat Chairperson

Dear Prospective Bidder:

| Bid Bulletin Ref. No. | Specific Page/Section in the Bidding Docs. | Query/Issue | BAC Response/Clarification |
|-----------------------------|--|--|--|
| BB3-1 | Page 84, | Can you provide detailed | Minimum Requirements: |
| | Section VII Technical Specifications | specifications for the processor, memory, hard drive, etc. since the | Form factor: 2U Rack. |
| | | specifications provided are very generic? | Processor: Intel Xeon E5- 2609 Quad Core 2.4Ghz, 10MB Cache |
| | | · | Chipset: Intel C602J Memory: 24 x 16GB PC3L- 10600 CL9 ECC DDR3 1333 MHz Expandable to 768 GB Memory protection ECC, Chipkill, memory mirroring, and |
| | | · | memory rank sparing. Storage: 10 x 300GB 10K 6Gbps SAS 2.5" SFF Hot |
| | | | Swap |
| | | , | RAID: Raid 5 with 512mb cache |
| | | | Optical drive: Ultra Slim Enhanced SATA Multi-Burner |
| | | | Network interfaces: Four integrated Gigabit Ethernet 1000BASE-T ports (RJ-45) with TCP Offload Engine (TOE) support, Wake on LAN support and NIC Teaming (load balancing and failover) |
| | | | PCI Expansion slots: 6 expansion Slots |
| | | | Ports: Two USB 2.0 and one DB-15 video on front. Four USB 2.0, one DB-15 video, one DB-9 serial, one RJ-45 systems management, four RJ-45 GbE network ports |
| | | | Cooling: Calibrated Vectored Cooling |

.

| | | | Power supply: redundant hot-swap Power Supply |
|-------|--|---|---|
| | | | Video: 16 MB memory integrated. Maximum resolution is 1600x1200 at 75 Hz with 16 M colors. |
| | | | Hot-swap parts: Hard drives, power supplies, and fans. |
| | Ŧ | | Systems management: UEFI, Integrated Management Module, Predictive Failure Analysis (includes Processor, Memory, Hard Drive, Power Supply, Fan's, Voltage Regulation Modules VRM), Light Path Diagnostics Security features Power-on password, administrator's password, Trusted Platform Module (TPM). |
| | | | OS: Not required. Linux OS will be installed. |
| | | | Warranty: Three (3) years on parts labor and onsite |
| | | | Other requirements: Bidder must be authorized service provider of the brand being offered |
| BB3-2 | Page 85, Section VII Technical Specifications | For the Cable Support, shall we provide the cables? | No. Just as long, it is cable supported and the connectivity can support the distance upto 328 feet or 100 meters. |
| BB3-3 | Page 84, Section VII Technical Specifications | Do the Technical Specifications include an Operating System (OS)? | No. |